THERMOCONTROLS

HOUSE OF INSTRUMENTS

Bimetallic Thermometers

Bimetallic Instruments are housed in Weatherproof IP 55 die cast Aluminium case or Pressed steel Non Weatherproof casing and are available in dial size of 25, 40, 50, 63 and 100 mm. These instruments are available in rigid stem type bottom and back connection direct mountings. The hazardous environments generally warrants use of these type of instruments.

Case & Bezel Material	**Die Cast Aluminium / Pressed Stainless Steel.**
Window	Sheet Glass
Mounting	Direct Mounting, Bottom / Back entry
Pointer	Micro Zero Adj. / Balanced Aluminium.
Dial	Aluminium, Black graduation on white background.
Stem Material	Brass Chrome Plated. SS 304, SS 316.
Stem Size	8/10/12 & 16mm
Stem Length	From 50 mm to 600 mm
Connection	1/4",3/8",1/2" BSP / NPT fixed or Adjustable Gland type.
Range	From -20°C to upto +300°C in standard ranges.
Accuracy	± 2% of the span (±1% optional)
Overrange Protection Fitments	20% of the span.

210 Malwa Ind. Co-op. Soc, Ltd, Patanwala Industrial estate, LBS Marg, Ghatkopar (West), Mumbai 400 086. Telfax: +91 22 25000844