



Double Window Sight Flow Indicator

Double Window type Sight Flow Indicator provides durable, quick reliable & economical way to verify the flow of liquids through industrial process lines. The round glass window area is large enough to provide better visibility. These are available in single window or double window constructions,

Casted or fabricated body & cover plate & the use of the toughened soda lime glass windows combined with selected seals which fit correctly in to properly machined seats which results in unusually high pressure ratings for double window sight flow indicators. This can also be used on vacuum applications. The glasses can be individually removed & replaced in this design.

These are available in plain models, rotator, flapper, drip tube types. Jacketed type also can be provided for heating & cooling applications.

Available sizes 15 MM to 200 MM in all types of flanged & threaded process connections. Material of Body available is SS 304, SS 316, MS, & PTFE / TFE / PFA lined for corrosive application. Toughened borosilicate or Plexi glasses can be supplied optionally. Max. op. Temp. 200°C

Glass	Toughened Soda Lime
Body & cover plate	S.S. 316 / S.S. 304 / C S / M.S.
Lining (optional)	PTFE / TFE / PFA coated for corrosive application
Gaskets	PTFE (Standard) / Neoprene - Viton - Silicon (Optional)
Nuts & Bolts	CS / ASTM A 194 & 193 / SS
Max. Op. Temp	200°C
Max. Op. Pressure	20 Kg/cm ²
Process Connection	Flanged as per A.S.A & B.S Standards or Screwed

210 Malwa Ind. Co-op. Soc, Ltd, Patanwala Industrial estate, LBS Marg, Ghatkopar (West), Mumbai 400 086. Telfax: +91 22 25000844