



### RTDs and Thermocouples Calibrator

<b>Fix Range Output , 12 Selectable</b>	-100, -50, -25, 000, +25, 50, 100, 150, 200, 250, 300, 400 °C for CAL-404 / CAL-403
	-200, -100, -50, 000, 50, 100, 150, 200, 250, 300, 400, 500, 600 °C for CAL-405 / CAL-406
<b>Variable Range Output</b>	-200°C to 600°C for CAL -403, CAL -406
<b>Accuracy</b>	±0.1% OHMS of FSR
<b>Compensation</b>	LWC (Long Wire Compensation) Of 100 Meter sensor cable.
<b>Include</b>	Test Leads, RTD Tables
<b>Option</b>	12 Selectable Ranges as per your requirement is possible.
<b>Operating Temp.</b>	0 to 50°C (RH < 80%)
<b>Supply</b>	Not required
<b>Box Size(HxWxD)</b>	Portable : 48 mm X 48 mm X 110 mm for CAL-404 / CAL-405 Table Top : 88 mm X 210 mm X 230 mm for CAL-403 / CAL-406

210 Malwa Ind. Co-op. Soc, Ltd, Patanwala Industrial estate, LBS Marg, Ghatkopar (West),  
Mumbai 400 086. Telfax: +91 22 25000844