



### Sanitary Pressure Gauges

These gauges are to meet special requirements of the Dairy, Food Processing, Pharmaceutical Industries and Filtration Applications etc

|                              |   |
|------------------------------|---|
| <b>Dial Size</b>             | <b>63mm and 100mm.</b>  |
| <b>Accuracy</b>              | ± 2% F.S.D. (± 1% optional)   |
| <b>Range</b>                 | Up to 40 kg/cm <sup>2</sup>   |
| <b>Over range protection</b> | 20% or as per class II of IS 3624.  |
| <b>Dial</b>                  | Aluminium Black Graduation on White Background  |
| <b>Casing</b>                | Stainless Steel 304   |
| <b>Bourdon &amp; Socket</b>  | Stainless Steel 316 or 304 .  |
| <b>Diaphragm Element</b>     | Stainless Steel 316   |
| <b>Diaphragm Unit</b>        | Stainless Steel 316 or 304  |
| <b>Connection</b>            | 1/4" BSP(M) or 50mm Triclover.  |
| <b>Optional Fitments</b>     | Glycerine Filling, Toughened / Acrylic window glass, Various grade of filling liquid to suit the process. |

210 Malwa Ind. Co-op. Soc, Ltd, Patanwala Industrial estate, LBS Marg, Ghatkopar (West),  
Mumbai 400 086. Telfax: +91 22 25000844